MIP12112

mini Pragma surface enclosure - 1 x 12 modules - plain door





Main

Milli	
Commercial Status	Commercialised
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	1
Type of front cover	Plain
Width	268 mm outside
Height	228 mm outside
Depth	102 mm outside

Complementary

Enclosure mounting	Surface
Total number of 18 mm modules	12
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	1 bare flange 1 trunking flange
Terminal block function	Earth / neutral
Number of terminal blocks	neutral terminal block with 8 screwed outgoers earth terminal block with 8 screwed outgoers
Distribution block outgoers	4 x 10 mm² for neutral 4 x 10 mm² for earth 3 x 6 mm² for neutral 3 x 6 mm² for earth 1 x 16 mm² for neutral 1 x 16 mm² for earth
Enclosure material	Front face: technoplastic Door: technoplastic Back part: technoplastic
Colour	Front face: white (RAL 9003) Door: white (RAL 9003)

Environment

Standards	EN 50102	
	IEC 529	
	IEC 60439-3	
	IEC 60670-24	
	IEC 60695-2-11	
Quality labels	IMQ	
Fire resistance	Front face : 650 °C	
	Door: 650 °C	
	Back part : 650 °C	
IP degree of protection	IP40	
IK degree of protection	IK07	
Ambient air temperature for operation	-2560 °C	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0901 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available 🖺 Download Влияние На Продукта Върху Околната Среда
Product end of life instructions	Need no specific recycling operations

