



<b>WATER HEATERS WITH TWO HEAT EXCHANGERS (S21) FOR VERTICAL MOUNTING ON THE WALL</b>				
<b>CHARACTERISTICS</b>				
Model	...	72270S21	72266S21	72280MS21
Volume range	L	100	120	150
Energy efficiency class	...	B	B	B
Rated pressure	MPa	0,8	0,8	0,8
Rated voltage	V~	230	230	230
Rated electrical power	W	2 (3)	2 (3)	2 (3)
Heat exchanger surface area	m <sup>2</sup>	0.36	0.53	0.53
Heat exchanger inside volume	L	1.72	2.58	2.58
Maximum thermal power heat exchanger (80-60°C)	kW	10	15	15
Standing loss	W	48	51	55
Weight	kg	38	49	55.5
<b>CONNECTIONS</b>				
1: Hot water outlet		G1/2 M	G1/2 M	G1/2 M
2: Cold water inlet - Drain		G1/2 M	G1/2 M	G1/2 M
3: Temperature indicator		-	-	-
4: Табло за управление		-	-	-
5: Flange with heating element		-	-	-
6: Heat exchanger 1 - Feed		G3/4 F	G3/4 F	G3/4 F
7: Heat exchanger 1 - Return		G3/4 F	G3/4 F	G3/4 F
8: Heat exchanger 2 - Feed		G3/4 F	G3/4 F	G3/4 F
9: Heat exchanger 2 - Return		G3/4 F	G3/4 F	G3/4 F
10: Socket for thermostat		G1/2 F	G1/2 F	G1/2 F
<b>DIMENSIONS</b>				
A	mm	1000	1165	1415
B	mm	915	1080	1330
C	mm	175	175	175
D	mm	460	460	460
E	mm	96	96	96
F	mm	474	474	474
G	mm	32	32	32
H	mm	280	270	270
I	mm	165	165	165
J	mm	450	630	630
M	mm	-	753	1003