



Main

Commercial Status	Commercialised
Range of product	Mini Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	1
Type of front cover	Translucid
Width	268 mm outside
Height	228 mm outside
Depth	102 mm outside

Complementary

Enclosure mounting	Surface
Total number of 18 mm modules	12
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	1 bare flange 1 trunking flange
Terminal block function	Earth / neutral
Number of terminal blocks	1 neutral terminal block with 8 screwed outgoers 1 earth terminal block with 8 screwed outgoers
Distribution block outgoers	4 x 10 mm ² for neutral 4 x 10 mm ² for earth 3 x 6 mm ² for neutral 3 x 6 mm ² for earth 1 x 16 mm ² for neutral 1 x 16 mm ² for earth
Enclosure material	Front face: technoplastic Door: technoplastic Back part: technoplastic
Colour	Door: translucid Front face: white (RAL 9003)

Environment

Standards	EN 50102 IEC 529 IEC 60439-3 IEC 60670-24 IEC 60695-2-11
Quality labels	IMQ
Fire resistance	Front face : 650 °C Door : 650 °C Back part : 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0901 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Влияние На Продукта Върху Околната Среда
Product end of life instructions	Need no specific recycling operations