



Main

Commercial Status	Commercialised
Range of product	Mini Pragma
Product or component type	Front face
Type of front plate	Transparent
Accessory / separate part category	Installation accessory

Complementary

Enclosure mounting	Flush
Type of front cover	Translucid
Number of horizontal rows	1
Number of 18 mm modules per row	12
Total number of 18 mm modules	12
Enclosure material	Front face: technoplastic Door: technoplastic
Width	294 mm outside
Height	252 mm outside
Depth	18 mm outside 13 mm wall
Colour	Front face :white (RAL 9003)

Environment

Standards	EN 50102 IEC 529 IEC 60695-2-11
Fire resistance	Front face : 650 °C Door : 650 °C
IK degree of protection	IK07
Ambient air temperature for operation	-25...60 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0901 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Влияние На Продукта Върху Околната Среда
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.